### TELECOM/DATACOM SYSTEM



# 6 Ports 10/100M Industrial UPOE Switch with 4x 10/100M RJ45 @UPOE 60W & 2x 10/100M RJ45

LIPOF6-4PU is a 4x 10/100M UPOE RJ45 port and 2x 10/100M RJ45 port Industrial UPOE switch. Its casing is IP40 rated and meet EMC industrial level 4 requirements. Features 3KV network port surge protection which is important for harsh outdoor environment and ensure the reliability of the uninterrupted system.



#### **FEATURES**

- 4x 10/100M UPOE RJ45@60W + 2x 10/100M RJ45
- Supports IEEE 802.3bt (Can be custom built for 95W)
- Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- IP40 protection
- Support Din Rail Mount
- RJ45 PortsAUTO Negotiation/AUTO MDI/MDIX
- MAC address table of the UPOE Switch with auto-learning and auto-aging
- Supports full-duplex and half-duplex auto-negotiation
- LED indicators for monitoring power, link, activity and UPOE status


#### **SPECIFICATIONS**

6Ports 10/100M Industrial UPOE Switch with 4x	10/100M DIAE @HDDE 60W 9. 2v 10/100M DIAE
Number of UPOE RJ45 ports (10/100BaseT)	4
Number of RJ45 ports (10/100BaseT)	2
Power Pin Assignment	1/2and 3/6 , or alternatively over 4/5(+) and 7/8 (-)
Performance Specifications	
Transmission Method	Store-And-Forward
Network Protocol and Standards	IEEE 802.3u
	IEEE 802.3x Flow Control
POE standard	IEEE802.3bt @ 60W (Optionally 95W)
POE power	70W per port
Enviornmental	
Operating temperature	-40 ~ 80° C
Storage temperature	-40 ~ 85° C
Operating hunidity	5 ~ 95% non condensation
Power Supply	AC 100-240V or DC 48-57V   65W
LED indicators	Power supply, network status, UPOE status
Physical	
Dimension	119 x 100 x 30mm
Weight	0.5kg

## TELECOM/DATACOM SYSTEM



#### FUNCTIONAL DIAGRAM



#### ORDERING INFORMATION

PN	DESCRIPTION
LIP0F6-4PU	6Ports 10/100M Industrial UPOE Switch with 4x 10/100M RJ45 @UPOE 60W & 2x 10/100M RJ45
PEA-52-250	Power adaptor 220VAC~52VDC: 250W